

RBM ShipWash

GENERAL PURPOSE MARINE CLEANER

IDEAL FOR general hold maintenance, washing down between sensitive cargos and cleaning around the deck, crane pedestals, superstructure, engine room and galley.

ShipWash, an aqueous compound, is a safe alternative to chlorinated and phosphate-based cleaning agents.

ShipWash quickly and efficiently removes light-to-medium chained hydrocarbons:

- Refined Oils
- Lubricating Fluids
- Greasy Dirt
- Residual Carbon/Soot

ShipWash integrates seven key properties to optimize cleaning performance:

- Solvency
- Surfactancy
- Emulsification
- Enhanced Wetting Properties
- Free-Rinsing Capability
- Rapid Dispersal of Moisture
- Corrosion Inhibition

PERFORMANCE

ShipWash is extremely versatile in its application. Utilizing powerful and natural surfactants and degreasers to aggressively break the bonds of a wide range of contaminants. By maintaining this separation, it provides faster wetting, aggressive penetration and overall better cleaning while rinsing totally free. ShipWash is revolutionary in its performance without compromising user safety or the environment.

PERSONAL & ENVIRONMENTAL SAFETY

In an effort to meet environmental and safety standards, common off the shelf solvents, surfactants and degreasers tend to sacrifice performance. ShipWash not only meets but often exceeds those standards while increasing performance requirements. Standard safety glasses and gloves are recommended as a safeguard against prolonged exposure.

ShipWash is completely biodegradable and, according to Bioassay toxicity test results, will not harm aquatic life.

DIRECTIONS

LIGHT DUTY: Spray on. Let penetrate for a few seconds. Wipe clean with a damp cloth.

HEAVY DUTY: Remove heavy or weathered deposits with pressure sprayer or brush before applying product. Spray ShipWash and let soak for 2 to 3 minutes. Additional soak time or some light scrubbing may be required for especially stubborn areas. Rinse well with highest pressure and warmest temperature available.

SUGGESTED DILUTION RATIOS	
RATIO	APPLICATION
1:1	Heavy Duty Spot Cleaning (ie Engine Room, Crane Pedestals)
2:1	Heavy Hold Cleaning
5:1	Light Hold/Deck Maintenance

Water: ShipWash

above dilution ratios are suggestions only.
Increase or decrease as required.